

REVISIONS			
REV.	DESCRIPTION	BY	DATE
A	INITIAL RELEASE	JJ	10/4/2010

THIS OPTION TO BE USED WITH ALL 8 SERIES SPIN PROCESSORS EXCEPT INDECKS

[37.3cm]
Ø14.7in

OPTIONAL SEISMIC BASE MOUNTING

[33cm]
Ø13.0in

OPTIONAL SEISMIC BASE MOUNTING

[1cm]
.38in

[1cm]
.38in


STANDARD FEET MOUNTING

[2.5cm]
1.0in
MINIMUM
CLEARANCE
ALL AROUND

[0.7cm]
Ø.265in
(4) PLCS

[35.6cm]
Ø14.0in
BOLT CIRCLE

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF LAURELL TECHNOLOGIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF LAURELL TECHNOLOGIES IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE		
DIMENSIONS ARE IN INCHES		DRAWN	JJ		TITLE: OPTION DIMENSIONAL DRAWING, 8 SEISMIC BASE
TOLERANCES:		CHECKED			
FRACTIONAL ±.015		ENG APPR.			
ANGULAR: MACH ± 1/2°		MFG APPR.			
TWO PLACE DECIMAL ±.01		Q.A.		SIZE DWG. NO. REV B 10077899 A	
THREE PLACE DECIMAL ±.005		COMMENTS:			
INTERPRET GEOMETRIC TOLERANCING PER:		ALL PARTS MUST BE CLEAN AND FREE OF BURRS. BREAK ALL SHARP EDGES, .015" RADIUS MAX.		SCALE: 1:8 WEIGHT: SHEET 1 OF 1	
MATERIAL					
NEXT ASSY	USED ON	FINISH			
APPLICATION		DO NOT SCALE DRAWING			